



High efficient and stable A multi-purpose machine

Fully Change QUALITY CHANGES THE WORLD

TOFDDF编辑器

福昕PDF编辑器

SELLING POINTS

Flexible Operation

High efficiency load sensitive system, minimum working device turning radius, deflective boom, flexible operation.

• Stable & Reliable

Imported engines, high strength structural parts, excellent lifting capacity, reliable work

• Various Configuration

Quick couple pipelines, two units of auxiliary pipelines, multi-function hand levers, various accesories could be equipped.


Safety & Comfortable


Suspension seat, silicone oil shock absorber, airconditioner, LED lights, working comfortably.

SOFFPDFSmt


Machine Dimesions (mm)

Standard





Operation range (mm)



		SY80U FPDF	
A	Overall length(in transportation)	7010	
В	Overall width(in transportation)	2200	
С	Overall height(in transportation)	2550	
D	Bulldozen plate height	410	
E	Standard track width	450	
F	Track gauge(in transportation)	1750	
G	Minimum ground clearance	365	
Н	Slewing radius of tail	1480	
I	Wheel gauge	2315	
J	Track length	2915	
	Performance parameters	Standard	
		SY80U	
0	peration weight kg		
		SY80U 8800	
Βι	peration weight kg	SY80U 8800	编辑器
Bı Ra	peration weight kg ucket capacity m³	SY80U 8800	编辑器
Bı Ra Tr	peration weight kg ucket capacity m³ ated power KW/rpm	SY80U 8800 0.28 53.7/2100 FDDF	编辑器
Bu Ra Tr SI	peration weight kg ucket capacity m ³ ated power KW/rpm raveling speed(high/low) km/h	SY80U 8800 0.28 53.7/2100 4.5/2.5	编辑器
Bu Ra Tr SI GI	peration weight kg ucket capacity m ³ ated power KW/rpm raveling speed(high/low) km/h ewing speed rpm	SY80U 8800 0.28 53.7/2100 PDF 4.5/2.5 10	编辑器
Bu Ra Tr SI Gi	peration weight kg ucket capacity m ³ ated power KW/rpm raveling speed(high/low) km/h ewing speed rpm radeability	SY80U 8800 0.28 53.7/2100 PDF 4.5/2.5 10 70%/35°	编辑器
Bu Ra Tr SI GI DI	peration weight kg ucket capacity m ³ ated power KW/rpm raveling speed(high/low) km/h ewing speed rpm radeability round pressure kPa	SY80U 8800 0.28 53.7/2100-PDF 4.5/2.5 10 70%/35° 37.9	编辑器

	Standard	
不同的下方	SY80U	
a Maximum digging height	7315	
b Maximum unloading height	5430	
c Maximum digging depth	4535	
d Maximum digging depth with vertical boon	n 2490	
e Maximum digging distance	7290	
f Maximum slewing radius	2435	
g Maximum height at maximum slewing radius	5490	
h Maximum ground clearance with bulldozing plate lifted up 480		
i Maximum cutting depth of bulldozing plate	325 DEPDE	
j Left deflective distance of boom	675	
k Right deflective distance of boom	585	

SANY Heavy Machinery Co.,LTD SANY Industrial Park,Dongcheng Avenue, Economic & Technical Development Zone,

SANY Industrial Park, Dongcheng Avenue, Economic & Technical Development Zone, KUNSHAN City, Jiangsu Province Zip code: 215300 Service hotline: 4008-28-2318 Complaint hotline: 4008-87-9318 Website: http://www.sanygroup.com



Due to continuous technical updates, materials and specifications are subject to change without prior notice The machine in the picture may include additional equipment.

ZJSYX0604CH

Printed in CHINA

福明市中国王编辑

福昕PDF编辑

福IFFPDF编辑